

Linea Max HE

Floor standing high efficiency combi boiler

SEDBUK 'B' RATED

60 LITRE BUILT IN TANK

NO VENTILATION REQUIRED

WHEEL IN FIXING JIG



Linea Max HE


Floor standing high efficiency combi boiler

SPECIFICATIONS	Linea Max HE
Central Heating	
Heat input (kW)	29
Maximum heat output @ 80°C/60°C (kW)	28.1
Maximum heat output @ 50°C/30°C (kW)	30.2
Domestic Hot Water	
Heat input (kW)	29
Flow rate - 35 °C rise (l/min)	18*
Flue Details (concentric)	
Maximum horizontal flue length (60/100mm)	2.0m
Maximum vertical flue length (60/100mm)	3.0m
Flue Details (twin pipes)	
Horizontal or vertical (80+80mm)	12m + 12m
Weight	
Dry weight (kg)	91
Electrical	
Voltage (V/Hz)	230/50
Connections	
Flow & return	22mm
Gas	15mm
DHW hot & cold	15mm
Safety valve	15mm
Condense	21mm


* Until thermal store depleted (or recovery to full performance in approximately 5 minutes)

** The appliance flue elbow on the Linea Max cannot be used with a vertical flue application and should be discarded.

UNIQUE WHEEL IN INSTALLATION



STEP 1
Connect pipework to base tray



STEP 2
Slide in boiler and connect unions at front

SEDBUK 'B' rated.

High domestic hot water flow rate makes Linea Max HE ideal for larger homes.

55% more flow rate than a combi of an equivalent output.

An integrated 60 litre thermal store boosts domestic hot water delivery to 18 litre/min.

The unique 'wheel-in' fixing jig allows pipes to be connected to a base tray without the boiler in place. Then simply slide boiler in and connect the unions at the front.

Anti-cycling control prevents wasteful on/off cycling of the boiler, eliminating unnecessary wear and tear.

The self-start programme protects the pump and motorised valve from sticking during long periods of inactivity.

Linea Max HE can be flued horizontally or vertically using Vokèra's concentric or twin flue systems making the boiler extremely versatile.

Built-in filling loop reduces installation time and material requirements.

Gas pressure set by gas valve, therefore no flue Gas Analyser required.

Linea Max HE reduces running costs by up to 35% more than a conventional boiler, helping to safeguard the environment.

Designed for easy installation. Standard Vokèra pipework layout enables trouble-free replacement of older Vokèra models.

Built-in frost protection, protects the appliance from damage during periods of cold weather.

Plated heat exchanger reduces the risk of scaling and comes with 5-year anti-scale warranty.



Registered Address: Vokèra Ltd Borderlake House, Unit 7 Riverside Industrial Estate, London Colney, AL2 1HG

Email: enquiries@vokera.co.uk Web: www.vokera.co.uk

Tel: 0844 391 0999 Fax: 0844 391 0998

Vokèra Ireland West Court, Callan, Co Kilkenny

Tel: 056 7755057 Fax: 056 7755060

Vokèra Limited reserve the right to change specification without prior notice. Consumers statutory rights are not affected. A Riello Group Company.
Company Reg No.: 1047779

Vokèra is a licensed member of the Benchmark scheme which aims to improve the standards of installation and commissioning of domestic hot water systems in the UK.